

# SPOTLITE™

## product sheet



### Suitable Controllers




### Powerful and affordable spotlight

#### SpotLite™

#### AX7

The younger brother of the SpotMax™ is the SpotLite™, a highly powerful, lightweight and cost-effective RGBW version of the brightest wireless spotlight on the market. Benefits include:

- RGBW CREE LEDs
- Dynamic Power-boost
- TruColor Calibration™
- IP65 Waterproof
- Waterproof Charging
- Long-life SAMSUNG Battery
- High-end Khatod Lenses
- Very high luminous power
- CRMX Wireless DMX






1,675 Lumen	up to 20 Hours of Operation	50,000 Hours LED Life	13° Beam Angle
6,250 Lux at 2m	IP65 Water Resistant	300m Range	RGBW CREE LEDs
W-DMX Controllable	4 Khatod Lenses	60W LED Power	Flood Diffuser Option



# SPOTLITE™

## product sheet

### SpotLite™




### Technical Specification

The SpotLite™ is the best all-round wireless spotlight on the market.

<b>Illuminants:</b>	4 x 15W RGBW CREE LEDs
<b>Total LED Power:</b>	60W
<b>Luminous Flux:</b>	1,675 lm (White)    678 lm (Green)
<i>typical values</i>	640 lm (Red)    223 lm (Blue)
<b>Illuminance:</b>	6,250 lx (White)    3,730 lx (Blue)
<i>typical values at 2m</i>	2,350 lx (Green)    1,990 lx (Red)
<b>Strobe:</b>	0-25Hz
<b>Beam Angle:</b>	13° (achieved through Khatod lenses)
<b>Battery:</b>	Built-in Samsung battery
<b>Battery Lifetime:</b>	70% capacity (after 300 charging cycles)
<b>Operation:</b>	up to 20hrs (seamless runtime)
<b>LED Lifetime:</b>	50,000 hours
<b>Charging Time:</b>	5-20 hours (depending on ambient temp)
<b>Working Voltage:</b>	Input 110-240V, 50/60Hz
<b>Wireless Module:</b>	868MHz receiver (US: 902-928MHz) 2.4GHz wireless module
<b>Range:</b>	300m (330yds)
<b>Wired DMX:</b>	No
<b>Astera Wireless DMX:</b>	Yes (with ART3 Transmitter)
<b>CRMX Wireless DMX:</b>	Yes (LumenRadio CRMX Wireless DMX)
<b>Power Connectors:</b>	2 (Neutrik Powercon True1 In & Out)
<b>Housing:</b>	Cast aluminium, Tempered glass
<b>IP Rating:</b>	IP65
<b>Relative Humidity:</b>	0-100% (non-condensing)
<b>Operating Temperature:</b>	0°-40°C (32°-104°F)
<b>Weight:</b>	6.10kg (13.4lbs)
<b>Dimensions:</b>	L279mm x H296mm x W253mm L10.9" x H11.6" x W9.9"
<b>Environment:</b>	Indoor / Outdoor
<b>Features:</b>	Temperature compensation, Dynamic power-boost, TruColor™ Calibration
<b>Included Accessories:</b>	Power Cord, 32° Flood Diffusor Sheet
<b>Also Available:</b>	Charging Case (holds 4), 17°x46° Wallwash Diffusor

### SpotLite™ Photometrics

Lux measurement at 4000K color temperature  
Standard 13° beam angle



**Spread (m):** The spread is the width of the light when it hits the flat surface.  
**Coverage Area (m<sup>2</sup>):** The coverage area is the size of the circular area that the light illuminates on the flat surface.  
**Lux:** is a measurement of the light intensity from a surface at any point.