



Mini ReLite Led T/D

Product code: F040C070A (T) | F040D070A (D)

KEY FEATURES

- Revitalize your 300/500/650 W Fresnel fixtures thanks to ReLite: your true retrofit LED relamping option
- Excellent white light quality with CRI > 90
- Flicker-free ideal for TV/Broadcast installations
- Linear dimming from 1% to 100% from traditional TRIAC AC or IGBT dimmers
- No color-shift with dimming
- Huge power savings (reduce your power consumption by over 90%) with almost no heat generated



SPECIFICATIONS

- Fixed white CCT: 3.200 K or 5.600 K
- Linear dimming from 1% to 100%: the stability of the fixture is guaranteed starting from 30/35 % of the dimmer channel (depending on the installation conditions)
- Flicker-free operation (dimming with constant current)
- Thermal protection
- IP rating: 20
- Instantly upgrade an existing Arri, ADB or De Sisti (and more)

LIGHT SOURCE

- Modular COB LED Tungsten or Daylight (CRI > 90)
- Average LED lifetime: a minimum of 80% of the initial luminous flux will be maintained after approx. 50.000 hours of usage (50.000 LM80)

PHYSICAL SIZE

- Depth: 73.7 mm (2.90 in)
- Width: 76.5 mm (3.01 in)
- Height: 77 mm (3.03 in)
- Height with connectors: 96 mm (3.78 in)
- Weight: 0.3 Kg (0.66 lbs)

ELECTRICAL SPECIFICATIONS AND CONNECTIONS

- Power supply: 90-240 V, auto-sensing, 50/60 Hz
- Max power consumption: 70 W
- Power consumption: 0.31 A at 230 V, Cosφ 0.98
- Pin connectors: GX9.5, GY9.5, G22

DRAWING SIZE

