

Provisional

ReLite Led Kit 150 VariWhite

KEY FEATURES

- 2.700 6.500 K continuously variable CCT
- CRI ≥ 95 (up to 97)
- Linear dimming from 1% to 100% via DMX
- Flicker-free ideal for TV/Broadcast installations
- No color-shift with dimming
- Huge power savings (reduce your power consumption by over 90%) with almost no heat generated
- No heat on your subject



SPECIFICATIONS

- CCT proportional control from 2.700 to 6.500 K
- Linear dimming from 1% to 100% via DMX
- No color shifts during dimming
- Flicker-free operation with LEDs frequency controlled via DMX or display from 640 to 1.500 Hz (different curves selectable)
- Operating Ta range (°C/F): from –20° to +45°C (from –4° to +113° F) thermal protection at 65°C/149°F
- IP rating: 20
- Instantly upgrade an existing Arri, ADB or De Sisti (and more)

LIGHT SOURCE

- Modular multiple LEDs (CRI ≥ 95 up to 97)
- Average LED lifetime: a minimum of 80% of the initial luminous flux will be maintained after approx. 50.000 hours of usage (50.000 LM80)

PHYSICAL SIZE (BOX)

- Length: 190 mm (7.48 in)
- Width: 110 mm (4.33 in)
- Height: 73 mm (2.87 in)
- Weight: 1.5 Kg (3.31 lbs)

CONTROL PROTOCOL AND PROGRAMMING


- USITT DMX512A
- DMX channels: 6 / 2 / 1
- Setting, addressing, testing and measurements via LEDs display
- RDM (Remote Device Management)


ELECTRICAL SPECIFICATIONS AND CONNECTIONS

- Power supply: 90-240 V, auto-sensing, 50/60 Hz
- In and Out PowerCon connectors
- Power consumption: depending on the LED module and the size/model of the fixture
- DMX data in/out: 5 pin locking XLR




DRAWING SIZE









DMX CHARTS

6 channels		2 channels		1 channel	
1	master dimmer	1	master dimmer	1	master dimmer
2	dimmer fine	2	white tone		
3	white tone				
4	white fine tuning				
5	strobe effect				
6	special function				